



Order form TRWS family

CUSTOMER	
Company	<input type="text"/>
Address	<input type="text"/>
Contact person	<input type="text"/>
Phone / email	<input type="text"/>


TRWS_10



TRWS_30



TRWS_E



TYPE	ORIFICE		
TRWS_10	<input type="checkbox"/> 200 cm ²		
TRWS_30	<input type="checkbox"/> 200 cm ²	<input type="checkbox"/> 314 cm ²	<input type="checkbox"/> 400 cm ²
TRWS_E	<input type="checkbox"/> 200 cm ²	<input type="checkbox"/> 314 cm ²	<input type="checkbox"/> 400 cm ²
Heating	<input type="checkbox"/> Y/N		
Cable fixed	<input type="checkbox"/> 2m (standard)	<input type="checkbox"/> <input type="text"/> m (custom lenght)	
Cable with connector M12	<input type="checkbox"/> 3m	<input type="checkbox"/> 10m	(Data 8-pin, Heating 4-pin)
Data protocol	<input type="checkbox"/> RS-485	<input type="checkbox"/> SDI-12	<input type="checkbox"/> ModBus

ACCESORIES			
Stand (Orifice above the groun)	<input type="checkbox"/> 1m	<input type="checkbox"/> 1.5m	<input type="checkbox"/> 2m
Mount adapter	<input type="checkbox"/> Y/N		
Wind shield	<input type="checkbox"/> Tretyakov	<input type="checkbox"/> Alter	
Bird protector	<input type="checkbox"/> Y/N	(Only for TRWS_10 & TRWS_30)	

